



| Model            | Indoor                    |  | JASA-Ce-H124A/R3 | JASA-Ce-H184A/R3 | JASA-Ce-H24A/R3 | JASA-Ce-H36A/R3 | JASA-Ce-H50A/R3 | JASA-Ce-H63A/R3 | JASA-Ce-H103A/R3 | JASA-Ce-H163A/R3 |
|------------------|---------------------------|--|------------------|------------------|-----------------|-----------------|-----------------|-----------------|------------------|------------------|
|                  | Outdoor                   |  | JASA-H124A/R3    | JASA-H184A/R3    | JASA-H24A/R3    | JASA-H36A/R3    | JASA-H50A/R3    | JASA-H63A/R3    | JASA-H103A/R3    | JASA-H163A/R3    |
| Power Supply     | V~ Ph Ph                  |  | 230-240/50.1     | 230-240/50.1     | 230-240/50.1    | 230-240/50.1    | 230-240/50.1    | 230-240/50.1    | 230-240/50.1     | 230-240/50.1     |
|                  | Cooling                   |  | 11800            | 17700            | 24300           | 34300           | 47800           | 58200           | 82000            | 125000           |
| Capacity         | Heating                   |  | 15800            | 19700            | 27200           | 37200           | 51200           | 61200           | 86000            | 129000           |
|                  | Rated Cooling Power Input |  | 1.80             | 2.30             | 3.20            | 4.30            | 5.80            | 6.80            | 9.20             | 13.80            |
| Electric Data    | Rated Heating Power Input |  | 1.80             | 2.30             | 3.20            | 4.30            | 5.80            | 6.80            | 9.20             | 13.80            |
|                  | Rated Cooling Current     |  | 8.3              | 9.5              | 13.5            | 17.5            | 24.5            | 29.5            | 40.5             | 60.5             |
| Performance      | Rated Heating Current     |  | 8.3              | 9.5              | 13.5            | 17.5            | 24.5            | 29.5            | 40.5             | 60.5             |
|                  | EER/COP                   |  | 12.5/3.33        | 12.5/3.41        | 12.5/3.41       | 12.5/3.41       | 12.5/3.41       | 12.5/3.41       | 12.5/3.41        | 12.5/3.41        |
| Indoor Unit      | Indoor Air Flow           |  | 600/1500/1500    | 850/1800/1800    | 1050/1800/1800  | 1450/2000/1800  | 1950/2000/1800  | 2350/2000/1800  | 3350/2000/1800   | 4850/2000/1800   |
|                  | Noise Level (dB(A))       |  | 36/36/33/28      | 44/44/40/36      | 49/49/45/41     | 55/55/51/47     | 61/61/57/53     | 67/67/63/59     | 73/73/69/65      | 79/79/75/71      |
| Outdoor Unit     | Net Dimension (W*H*D)     |  | 870*595*235      | 870*665*235      | 1030*775*300    | 1360*775*300    | 1720*775*300    | 1720*775*300    | 2320*775*300     | 3320*775*300     |
|                  | Net Weight (Gross Weight) |  | 25.5/25.5        | 26.5/26.5        | 28.5/28.5       | 32.5/32.5       | 40.5/40.5       | 42.5/42.5       | 58.5/58.5        | 82.5/82.5        |
| Refrigerant Type | Refrigerant               |  | R410A            | R410A            | R410A           | R410A           | R410A           | R410A           | R410A            | R410A            |
|                  | Refrigerant Charge        |  | 3.0/3.0          | 3.0/3.0          | 3.0/3.0         | 3.0/3.0         | 3.0/3.0         | 3.0/3.0         | 3.0/3.0          | 3.0/3.0          |
| Refrigerant Pipe | Liquid Side               |  | 1/4"             | 1/4"             | 1/4"            | 1/4"            | 1/4"            | 1/4"            | 1/4"             | 1/4"             |
|                  | Gas Side                  |  | 3/8"             | 1/2"             | 5/8"            | 5/8"            | 5/8"            | 5/8"            | 5/8"             | 5/8"             |
| Refrigerant Pipe | Max. Length               |  | 25               | 25               | 40              | 40              | 55              | 55              | 85               | 85               |
|                  | Max. Height               |  | 15               | 15               | 20              | 20              | 25              | 25              | 35               | 35               |

| Indoor Dimension |      |     |      |     |
|------------------|------|-----|------|-----|
| Model            | A    | B   | C    | E   |
| JASA-Ce-H124A/R3 | 870  | 235 | 870  | 865 |
| JASA-Ce-H184A/R3 | 870  | 235 | 870  | 865 |
| JASA-Ce-H24A/R3  | 870  | 235 | 870  | 865 |
| JASA-Ce-H36A/R3  | 1030 | 235 | 1140 | 865 |
| JASA-Ce-H50A/R3  | 1370 | 235 | 1510 | 865 |
| JASA-Ce-H63A/R3  | 1570 | 235 | 1510 | 865 |

| Outdoor Dimension |      |     |     |     |     |      |
|-------------------|------|-----|-----|-----|-----|------|
| Model             | A    | B   | C   | D   | F   | G    |
| JASA-H124A/R3     | 878  | 376 | 586 | 580 | 345 | 887  |
| JASA-H184A/R3     | 878  | 376 | 586 | 580 | 345 | 887  |
| JASA-H24A/R3      | 878  | 376 | 586 | 580 | 345 | 887  |
| JASA-H36A/R3      | 1038 | 376 | 686 | 580 | 345 | 887  |
| JASA-H50A/R3      | 1378 | 427 | 786 | 630 | 395 | 1002 |
| JASA-H63A/R3      | 1578 | 530 | 820 | 630 | 485 | -    |
| JASA-H103A/R3     | 1578 | 530 | 820 | 630 | 485 | -    |
| JASA-H163A/R3     | 1578 | 530 | 820 | 630 | 485 | -    |
| JASA-H203A/R3     | 1578 | 530 | 820 | 630 | 485 | -    |

