

# AL Floor Standing

## Technical Specifications



| Model            |                           |          | JASA-FI-H24A4/AL   | JASA-FI-H36A4/AL                                                                             | JASA-FI-H60A5/AL    | JASA-FI-H96A5/AL                                                                             |
|------------------|---------------------------|----------|--------------------|----------------------------------------------------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------|
|                  |                           |          | Fixed Speed        | Inverter  | Fixed Speed         | Inverter  |
| Power Supply     |                           | V~,Hz,Ph | 220~240,50,1       | 220~240,50,1                                                                                 | 380~415,50,3        | 380~415,50,3                                                                                 |
| Capacity         | Cooling                   | W        | 7500               | 10550                                                                                        | 15500               | 28100                                                                                        |
|                  | Heating                   | W        | 8100               | 10850                                                                                        | 17500               | 30000                                                                                        |
| Performance      |                           | EER/COP  | 3.00/3.45          | 3.15/3.68                                                                                    | 2.65/3.18           | 2.44/3.00                                                                                    |
| Electric Data    | Rated Cooling Power Input | W        | 2500               | 3350                                                                                         | 5850                | 11500                                                                                        |
|                  | Rated Heating Power Input | W        | 2350               | 2950                                                                                         | 5500                | 10000                                                                                        |
|                  | Rated Cooling Current     | A        | 11.40              | 15.50                                                                                        | 11.35               | 19.70                                                                                        |
|                  | Rated Heating Current     | A        | 10.80              | 15.00                                                                                        | 11.60               | 17.10                                                                                        |
| Indoor           | Indoor Air Flow           | m/h      | 1200/1100/1000/850 | 1850/1700/1550/1400                                                                          | 1850/1700/1550/1400 | 4000                                                                                         |
|                  | Noise Level               | dB(A)    | 46/44/41/37        | 52/50/48/45                                                                                  | 54/52/49/47         | 63/60/57                                                                                     |
|                  | Outline Dimension (Φ×D)   | mm       | 507×1770×320       | 587×1882×394                                                                                 | 587×1882×394        | 1200×1850×400                                                                                |
|                  | Package Dimension (W×H×D) | mm       | 623×1988×440       | 738×2153×545                                                                                 | 738×2153×545        | 1363×2013×513                                                                                |
|                  | Weight Net/Gross          | kg       | 40.0/52.0          | 58.0/80.5                                                                                    | 59.0/81.5           | 129.0/141.0                                                                                  |
| Outdoor          | Noise Level               | dB(A)    | 56                 | 63                                                                                           | 61                  | 63                                                                                           |
|                  | Outline Dimension (W×H×D) | mm       | 955×396×700        | 1000×427×746                                                                                 | 958×412×1350        | 940×460×1615                                                                                 |
|                  | Package Dimension (W×H×D) | mm       | 1029×458×750       | 1077×480×785                                                                                 | 1027×443×1395       | 1038×578×1770                                                                                |
|                  | Weight Net/Gross          | kg       | 60.0/64.5          | 60.0/65.0                                                                                    | 117/127             | 160/174                                                                                      |
| Refrigerant Pipe | Refrigerant Type          | g        | R410A/1700         | R410A/2800                                                                                   | R410A/3900          | R410A/8000                                                                                   |
|                  | Gas                       | inch     | 1/4"               | 1/4"                                                                                         | 3/8"                | 3/8"                                                                                         |
|                  | Liquid                    | inch     | 5/8"               | 5/8"                                                                                         | 5/8"                | 7/8"                                                                                         |
|                  | Max Length                | m        | 30                 | 30                                                                                           | 40                  | 50                                                                                           |
|                  | Max Height                | m        | 20                 | 20                                                                                           | 30                  | 30                                                                                           |

| Indoor Dimension |      |      |     |
|------------------|------|------|-----|
| Model            | W    | H    | D   |
| JASA-FI-H24A4/AL | 507  | 1770 | 320 |
| JASA-FI-H36A4/AL | 587  | 1882 | 394 |
| JASA-FI-H60A5/AL | 587  | 1882 | 394 |
| JASA-FI-H96A5/AL | 1200 | 1850 | 400 |

| Outdoor Dimension |      |     |      |     |     |      |     |
|-------------------|------|-----|------|-----|-----|------|-----|
| Model             | A    | B   | C    | D   | E   | F    | G   |
| JASA-FI-H24A4/AL  | 897  | 340 | 700  | 560 | 396 | 965  | 364 |
| JASA-FI-H36A4/AL  | 920  | 370 | 790  | 610 | 427 | 1003 | 395 |
| JASA-FI-H60A5/AL  | 1000 | 370 | 1363 | 620 | 427 | 1089 | 399 |
| JASA-FI-H96A5/AL  | 940  | 460 | 1616 | 610 | 530 | -    | 486 |

