



Jet-Air
Cool, Warm & Collected

QPLUS

Inverter Duct



Higher efficiency and comfort

DC inverter compressor and DC inverter fan motor gives higher efficiency and comfort.



Extensive range

Wide capacity from 12,000 to 60,000 BTU/h, single phase and three phase.



Flexible Air Intake

Air intake direction can be adjusted from the rear (as standard) or into bottom (as option) at site.



Built-in Drain Pump

Built in drain pump can lift the condensate water up to 1 000 mm.



Jet-Air APP

Wired controller with WIFI inside enables you to control your air conditioner via cellphone at any time.




Central control & BMS

Central control & BMS are available with optional accessories.



(Optional)





AXI Inverter Duct

Technical Specifications



Model	Indoor	JASA-HI-H12A4/AXI				JASA-HI-H18A4/AXI				JASA-HI-H24A4/AXI				JASA-HI-H36A4/AXI				JASA-HI-H48A4/AXI				JASA-HI-H48A5/AXI				JASA-HI-H60A4/AXI				JASA-HI-H60A5/AXI							
	Outdoor	JASA-H12A4/AXI				JASA-H18A4/AXI				JASA-H24A4/AXI				JASA-H36A4/AXI				JASA-H48A4/AXI				JASA-H48A5/AXI				JASA-H60A4/AXI				JASA-H60A5/AXI							
Power Supply	V~, Hz, Ph	220~240, 50, 1				220~240, 50, 1				220~240, 50, 1				220~240, 50/60, 1				220~240, 50/60, 1				220~240, 50/60, 1				220~240, 50/60, 1				220~240, 50/60, 1				220~240, 50/60, 1			
	Capacity	Cooling	W				3517				5300				6700				10500				13500				14000				16000				16000		
Performance	Heating	W				4000				5800				7600				10700				14100				17500				18000				18000			
	EER/COP	W				3.52/4.21				3.40/4.30				3.03/3.2				3.62/3.96				3.29/3.62				3.04/3.64				3.3/3.7				2.9/3.6			
Electric Data	Max. Cooling Power Input	W				1450				1780				2420				3200				4200				5250				6400				6400			
	Max. Heating Power Input	W				1450				1780				2540				3200				4200				5250				6400				5700			
Indoor Unit	Cooling Current Input	A				8				8				12				14				19.17				24				24				11			
	Heating Current Input	A				8.5				8.5				12				14				18.63				24				24				11			
Indoor Unit	Indoor Air Flow (SSH/M/L)	m³/h				650/600/500/440				1100/1000/900/700				1100/1000/900/700				1350/1250/1050/850				1900/1700/1500/1300				2200/2500/2200/1800				2800/2500/2200/1800							
	Noise Level (SSH/M/L)	dB(A)				35/33/31/28				39/36/33/31				39/38/35/34				44/42/40/38				45/43/41/39				46/45/44/42				47/45/43/40				47/44/43/40			
Outdoor Unit	Outline Dimension (W×H×D)	mm				700×198×450				900×198×450				900×198×450				900×260×655				1200×655×260				1340×655×260				1400×700×300				1400×700×300			
	Package Dimension (W×H×D)	mm				938×260×555				1138×260×555				1138×260×555				1115×320×772				1415×772×320				1568×770×323				1601×813×365				1601×813×365			
Outdoor Unit	Weight Net/Gross	Kg				13.5/17.5				17/21.5				17/21.5				29.5/34.5				35.5/41				43/49				54/60				53/60			
	Noise Level	dB(A)				50				51				58				59				59				59				60				60			
Outdoor Unit	Outline Dimension (W×H×D)	mm				732×555×330				732×555×330				958×660×402				958×660×402				1000/746/427				940/820/370				940/820/370				940/820/370			
	Package Dimension L×H×W	mm				794×615×376				794×615×376				1032×737×456				1032×737×456				1080/810/483				1095/955/500				1095/955/500				1093/497/885			
Refrigerant Pipe	Weight Net/Gross	Kg				24.5/27				27.5/30				38.5/42.5				45/49				51.5/56.5				73/86				83/90				83/90			
	Refrigerant Type	g				R32/630				R32/800				R32/1000				R32/1400				R32/2100				R32/2800				R32/2900				R32/2900			
Refrigerant Pipe	Gas	Inch				"1/2"				"3/8"				"5/8"				"5/8"				"5/8"				"5/8"				"5/8"				"5/8"			
	Liquid	Inch				"1/4"				"1/4"				"1/4"				"1/4"				"1/4"				"3/8"				"3/8"				"3/8"			
Refrigerant Pipe	Max Distance Length	m				20				30				30				30				50				75				75				75			
	Max Distance Height	m				10				15				15				20				30				30				30				30			

Model	Indoor Dimension										Outdoor Dimension									
	A	B	C	D	E	F	G	H	I	J	A	B	C	D	E	F	G	H	I	J
JASA-HI-H12A4/AXI	740	355	700	198	450	482	137	527	630	198	732	330	555	455	310	675	285			
JASA-HI-H18A4/AXI	930	354	900	198	450	483	140	740	802	198	732	330	555	455	310	675	285			
JASA-HI-H24A4/AXI	940	355	900	198	450	470	140	740	802	198	958	402	660	570	371	889	340			
JASA-HI-H36A4/AXI	942	590	900	260	655	692	215	740	871	234	958	402	660	570	371	889	340			
JASA-HI-H48A4/AXI	1242	590	1200	260	655	688	215	1040	1171	234	1000	427	746	610	396	920	370			
JASA-HI-H60A4/AXI	1440	500	1400	300	700	754	197	1151	1362	264	1020	427	820	635	396	940	370			
JASA-HI-H48A5/AXI	1381	595	1340	260	655	697	215	1153	1188	220	1020	427	820	635	396	940	370			
JASA-HI-H60A5/AXI	1440	500	1400	300	700	754	197	1151	1362	264	1020	427	820	635	396	940	370			

